

SPECIFICATIONS

General Wallcovering Specifications:

- **Weight:** 20 oz/ly (452 gr/m2)
- **Width:** 52/54" (132/137cm)
- **Backing:** Osnaburg
- **Installation:** Reverse hang / Random match
- **Performance:** Custom colors, weights, widths, and microventing available.

Fire Safety:

- Class A - ASTM E-84(GRC)
- Passes NFPA 286 Corner Burn
- NFPA 101 Life Safety Code
- CAN/ULC S102
- BS476 Class 0

Environmental and Health:

- Phthalate Free
- Health Product Declaration
- Environmental Product Declaration
- Meets State of Washington Building Specification for Indoor Air Quality
- Meets California Section 01350 Indoor Air Quality Standard
- Aggressive manufacturing materials recovery and reuse program
- Highly cleanable water-based inks
- Free of PBDE's (Brominated Flame Retardants)

USGBC LEED Support:

- Supports USGBC LEED v4.1 Criteria
- Materials and Resources; Building Product Disclosure and Optimization (includes Recycled Content; Construction Waste Management; HPD's)
- Indoor Environmental Quality; Low emitting materials

Moisture, Mold, and Mildew:

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and the wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. However, no additives will prevent mold growth if moisture accumulates and its sources aren't eliminated.

For further protection against mold growth. We offer a unique state of the art technology that "breathes," helping manage moisture in walls.